SensorsONE
Measurement Instrumentation Products

DMP 320

Precision Pressure Transmitter with Fast Response Time

Stainless Steel Sensor

accuracy according to IEC 61298-2:
0.1 % FSO

Nominal pressure

- from 0...100 mbar up to 0...600 bar

Output signal

3-wire: 0.1 … 10 V
4 … 20 mA
others on request

Special characteristics

- extremely fast response time ≤ 0.5 msec
- internal sample rate 10 kHz
- accuracy 0.1 % FSO
- excellent thermal behaviour
- outstanding long term stability

Optional versions

- customer specific versions

DMP 320 stands for speed and precision.

With a response time of ≤ 0.5 msec and a sampling rate of 10 kHz, the pressure transmitter was designed for applications, in which an extremely fast and exact pressure measuring is required. Pressure curves, peaks and hits can be monitored and evaluated exactly.

The signal processing of the sensor signal is done by newly developed digital electronics, which detect the signal with a sampling rate of 10 kHz. Sensor-specific deviations such as non-linearity, hysteresis and temperature errors are compensated actively.

Preferred areas of use are

- Plant and machine engineering
- Energy industry

Input pressure range											
Nominal pressure gauge [bar]	-1…0	0.10	0.16	0.25	0.40	0.60	1	1.6	2.5	4	6
Nominal pressure absolute [bar]	-	-	-	-	0.40	0.60	1	1.6	2.5	4	6
Overpressure [bar]	5	0.5	1	1	2	5	5	10	10	20	40
Burst pressure ≥ [bar]	7.5	1.5	1.5	1.5	3	7.5	7.5	15	15	25	50

Nominal pressure gauge /abs [bar]	10	16	25	40	60	100	160	250	400	600
Overpressure [bar]	40	80	80	105	210	600	600	1000	1000	1000
Burst pressure ≥ [bar]	50	120	120	210	420	1000	1000	1250	1250	1250
Vacuum resistance	p_N ≥ 1 bar: unlimited vacuum resistance p_N < 1 bar: on request									

Output signal / Supply	
3-wire voltage	0.1 ... 10 V / V_S = 14 ... 30 V_{DC}
3-wire current	4 ... 20 mA / V_S = 14 ... 30 V_{DC}
Performance	
Accuracy [1]	nominal pressure ≥ 0.25 bar: ≤ ± 0.10 % FSO nominal pressure < 0.25 bar: ≤ ± 0.25 % FSO
Permissible load	current 3-wire: R_{max} = 500 Ω voltage 3-wire: R_{min} = 10 kΩ
Influence effects	supply: 0.05 % FSO / 10 V load: 0.05 % FSO / kΩ
Long term stability	≤ ± 0.1 % FSO / year at reference conditions
Response time	≤ 0.5 msec
[1] accuracy according to IEC 61298-2 – limit point adjustment (non-linearity, hysteresis, repeatability)	
Thermal effects (offset and span)	
Tolerance band	≤ ± 0.2 % FSO
TC, average	± 0.02 % FSO / 10 K
in compensated range	-20 ... 80 °C
Permissible temperatures	
Medium	-40 ... 125°C
Electronics / environment	-40 ... 85°C
Storage	-40 ... 100°C
Electrical protection	
Short-circuit protection	permanent
Reverse polarity protection	no damage, but also no function
Electromagnetic compatibility	emission and immunity according to EN 61326
Mechanical stability	
Vibration	20 g RMS / 10 ... 2000 Hz according to DIN EN 60068-2-6
Shock	500 g / 1 msec half sine according to DIN EN 60068-2-27
Materials	
Pressure Port	stainless steel 1.4404 (316 L)
Housing	stainless steel 1.4404 (316 L)
Option compact field housing	stainless steel 1.4301 (304) cable gland M12x1.5, brass, nickel plated (clamping range 2 … 8 mm)
Seals	standard: FKM options: EPDM others on request
Diaphragm	stainless steel 1.4435 (316 L)
Media wetted parts	pressure port, seals, diaphragm
Miscellaneous	
Current consumption	3-wire voltage: < 30 mA 3-wire current: < 55 mA
Weight	approx. 200 g
Installation position	any [2]
Operational life	100 million load cycles
CE-conformity	EMC Directive: 2014/30/EU Pressure Equipment Directive: 2014/68/EU (module A) [3]

[2] Pressure transmitters are calibrated in a vertical position with the pressure connection down. If this position is changed on installation there can be slight deviations in the zero point for pressure ranges p_N ≤ 1 bar.

[3] This directive is only valid for devices with maximum permissible overpressure > 200 bar

Wiring diagram

3-wire-system (current / voltage)



Pin configuration

Electrical connection	ISO 4400	Binder 723 (5-pin)	M12x1 / metal (4-pin)	compact field housing	cable colours (IEC 60757)
					
Supply +	1	3	1	V_S+	WH (white)
Supply –	2	4	2	V_S-	BN (brown)
Signal +	3	1	3	S+	GN (green)
Shield	ground pin ⏚	5	4	GND	GNYE (green-yellow)

Electrical connections (dimensions mm / in)



ISO 4400
(IP 65)



Binder series 723, 5-pin
(IP 67)



M12x1, 4-pin
(IP 67)



compact field housing
(IP 67)



cable outlet
with PVC-cable (IP 67) [4]



cable outlet, cable with
ventilation tube (IP 68) [5]

⇨ **universal field housing stainless steel 1.4404 (316 L) with cable gland M20x1.5 (ordering code 880) and other versions on request**

[4] standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C)
[5] different cable types and lengths available, permissible temperature depends on kind of cable

Dimensions (mm / in)



* for nominal pressure p_N > 40 bar the length of devices increases by 9 mm

Mechanical connections (dimensions mm / in)



G1/2" DIN 3852



G1/2" EN 837



1/2" NPT



G1/4" DIN 3852



G1/4" EN 837



1/4" NPT



G1/2" open port DIN 3852
(p_N ≤ 40 bar)

⇨ metric threads and other versions on request

© 2025 The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

Ordering code DMP 320

DMP 320 □□□-□□□□-□-□-□□□-□□□-□-□□□

| | | |